

**ORIGINAL HEIDELBERG
CYLINDER $22\frac{1}{2} \times 30\frac{1}{4}$ "/ $22\frac{1}{2} \times 32\frac{1}{4}$ "**

OPERATION MANUAL



**HEIDELBERGER DRUCKMASCHINEN
AKTIENGESELLSCHAFT**

SALES AND SERVICE THROUGHOUT THE WORLD

THIS BOOK SHOULD BE KEPT IN THE MACHINE ROOM

The operation of the Original Heidelberg Cylinder $22\frac{1}{2} \times 30\frac{1}{4}$ " and $22\frac{1}{2} \times 32\frac{1}{4}$ " is very simple. A proof may be seen in the fact that by the end of 1967 approximately 45 000 Original Heidelberg Cylinders had been installed all over the world and enthusiastically received.

The purpose of this instruction manual is to enable printers to obtain the maximum advantage from the machine. We hope that it will not only ensure thorough maintenance of the machine but will promote a better understanding of progressive methods in preparation of the forme and make-ready, the use of inks and the care of rollers.

By following our advice, tested and proved the world over, the printer will obtain the maximum efficiency from his Original Heidelberg Cylinder.

**HEIDELBERGER DRUCKMASCHINEN
AKTIENGESELLSCHAFT**

CONTENTS

Table of most important adjustments for various stock	9	Cleaning the air filter in the suction and the air pump	36
Specifications for the Original Heidelberg Cylinder 22½ x 30¼" / 22½ x 32¼"	10	Cleaning the filter of the air pump for the spraying device	37
Floor plan	11	Cleaning the main pinion, gear racks and crankshaft area	37
Oil drip pan	12		
 The design		 Maintenance at longer intervals	
Original Heidelberg Cylinder	14	Readjustment of flywheel brake	40
Reduction to the minimum of make-ready time	17	Exchange of V-belts	41
Cutting down unproductive time	18	Cleaning the suction and blast air pump for feeder	42
 Printing in general		 Operating the machine	
Correct forme alignment	22	Control of the machine	44
Block justification	22	Electrical control equipment	44
Mounting of blocks	23	Operating electric controller	44
Wood mounts	23	Forme and roller guard	45
Lead or iron mounts	23	Single lever control for Stop-Run-Paper-Impression	45
Light metal mounts	23	Stopping the machine	47
Honeycomb base	23	Two step pulley drive	48
Slur	25	Turning the machine by hand	49
Slur — ink too thin	25	Treatment of rubber rollers	49
Slur — ink too tacky	25	Treatment of plastic rollers	51
Slur — caused by forme rollers	25	Inking system	52
Slur — caused by badly mounted blocks	26	When does the printer use 2, 3 or 4 forme rollers?	53
Slur — caused by high or low blocks	26	Inserting rollers in the machine	55
Remedies	28	Inserting the forme rollers	55
Pre-make-ready of forme	29	Taking out of the forme rollers	56
Inking	29	Taking out of the distributor rollers	56
		Adjustment of the vibrator	56
 Maintenance		Adjusting the distributor rollers	57
Running-in the machine	32	Adjusting the forme rollers	58
Lubrication of the machine	32	Disengaging rollers	60
Daily, weekly, and semi-annual oiling	32	Regulating the knife and ink strip	61
Oil lubrication	32	Engaging and disengaging ink supply	62
Grease lubrication	33	Regulating the reciprocating rollers	63
Central lubrication	34	Operating the roller washing device	64
Gear box oil bath	35	Cleaning the duct and the ductor blade	68
Cleaning the machine	35	Cleaning the splash guard	68